

CRF230L



Ever wonder what's over the next hill? The road registerable CRF230L - small in size, big on fun. Compact, lightweight and designed to go anywhere. Thanks to its modest size and weight, the CRF230L is able to fulfill an amazing variety of roles.

SPECIFICATIONS

Engine	223cc 4-stroke, single-cylinder, air-cooled SOHC
Bore & Stroke	65.5 x 66.2mm
Compression Ratio	9.0:1
Valve Train	SOHC; 2-valve
Carburetion	30mm
Ignition	CDI Battery
Transmission	6-speed
Starter	Electric
Dimensions	2,080mm x 825mm x 1,110mm
Final Drive	#520 O-ring sealed chain
Front Suspension	37mm leading axle Showa fork; 228mm travel
Rear Suspension	Pro-Link Showa single shock with spring preload adjustability; 160mm travel
Brakes	Front: 240mm hydraulic disc with dual-piston caliper and sintered metal pads Rear: 220mm hydraulic disc with single-piston caliper and sintered metal pads
Tyres	Front: 2.75 - 21 inch Rear: 120/80 - 18 inch
Wheelbase	1,339mm
Rake (Castor Angle)	-
Trail	103mm
Seat Height	805mm
Ground Clearance	245mm
Fuel Capacity	8.7 litres (including 2.6 litre reserve)
Kerb Weight	122kg
Warranty Period	12 months